

## METHODS OF DELIVERY

### LIQUEFIED

#### In cylinders

capacity l H <sub>2</sub> O	outside diameter mm	height* mm	gross weight* kg	contained gas kg
14	168	960	30.0	10.5
20	203	960	44.5	15.0
27	203	1230	54.5	20.2
40	203	1670	77.0	30.0
50	227	1680	98.0	37.5

\* with valve and cover cap

*Other capacities are available upon request*

#### In packs of cylinders

cylinders No.	dimensions (LxWxH) mm	gross weight kg	contained gas kg
16	1030x1030x1935	1710	480

*Other capacities are available upon request*

#### In tanks

Capacity l:

1.400 - 3.000 - 6.000 - 12.000 - 22.000 - 32.000 - 50.000

Cylinder colour:

*body grey RAL 7031*

*shoulder grey RAL 7037*

(European Norm UNI-EN 1089-3)

## CONVERSION TABLE

1 m<sup>3</sup> = 1.813 kg = 2.391 l

1 kg = 0.552 m<sup>3</sup> = 1.319 l

1 l = 0.431 m<sup>3</sup> = 0.758 kg

*m<sup>3</sup>: gaseous at 15°C and 98 kPa (735.5 mm Hg)*

*l: unit of volume in the liquid state*