

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

SDS reference: 00061_LIQ





SECTION 1: identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Helium (refrigerated liquid)

SDS no : 00061_LIQ

Chemical description : Helium (refrigerated liquid)

CAS-No.: 7440-59-7 EC-No.: 231-168-5 EC Index-No.: ---

Registration-No. : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : He

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.

Test gas/Calibration gas.

Purge gas, diluting gas, inerting gas.

Purging.

Shield gas for welding processes.

Use for manufacture of electronic/photovoltaic components.

Laboratory use.

Contact supplier for more information on uses.

Uses advised against : Do not inhale product on purpose because of the risk of asphyxiation.

1.3. Details of the supplier of the safety data sheet

Company identification : SIAD S.p.A.

Via San Bernardino, 92 I-24126 Bergamo Italia

+39 035 328111 www.siad.com

siad_reach_clp@siad.com

1.4. Emergency telephone number

Emergency telephone number : Linea verde S.E.T. - from Italy 800452661 - International +39 0362512868 - 24 hours a day,

365 days a year

SECTION 2: hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Gases under pressure : Refrigerated liquefied gas H281

2.2. Label elements

+39 035 328111

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

SIAD S.p.A. EN (English) SDS Ref.: 00061_LIQ
Via San Bernardino, 92 I-24126
Bergamo Italia

1/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

SDS reference: 00061_LIQ

Hazard pictograms (CLP)

GHS04

Signal word (CLP) : Warning

Hazard statements (CLP) : H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

Precautionary statements (CLP)

- Prevention: P282 - Wear cold insulating gloves and either face shield or eye protection.

- Response : P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate

medical advice / attention.

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

: Asphyxiant in high concentrations.

Contact with liquid may cause cold burns/frostbite.

SECTION 3: composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Helium (refrigerated liquid)	(CAS-No.) 7440-59-7 (EC-No.) 231-168-5	100	Press. Gas (Ref. Liq.), H281
	(EC Index-No.) (Registration-No.) *1		

Contains no other components or impurities which will influence the classification of the product.

- *1: Listed in Annex IV / V REACH, exempted from registration.
- *2: Registration deadline not expired.
- *3: Registration not required: Substance manufactured or imported < 1t/y.

3.2. Mixtures : Not applicable

SECTION 4: first aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing

stopped.

- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain

medical assistance.

- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

SDS reference: 00061_LIQ

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.

Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5: firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat

radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and

drainage systems.

If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

If leaking do not spray water onto container. Water surrounding area (from protected position)

to contain fire.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters

In confined space use self-contained breathing apparatus.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659 - Protective gloves for

firefighters.

SECTION 6: accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Try to stop release.

Evacuate area.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to

be safe.

Use protective clothing.

Ensure adequate air ventilation.

Act in accordance with local emergency plan.

Stay upwind

Oxygen detectors should be used when asphyxiating gases may be released.

6.2. Environmental precautions

: Try to stop release.

Liquid spillages can cause embrittlement of structural materials.

6.3. Methods and material for containment and cleaning up

 SIAD S.p.A.
 EN (English)
 SDS Ref.: 00061_LIQ
 3/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

SDS reference: 00061_LIQ

: Ventilate area.

6.4. Reference to other sections

: See also sections 8 and 13.

SECTION 7: handling and storage

7.1. Precautions for safe handling

Safe use of the product

 The product must be handled in accordance with good industrial hygiene and safety procedures.

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

Do not smoke while handling product.

Use only properly specified equipment which is suitable for this product, its supply pressure and

temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis.

Do not breathe gas.

Avoid release of product into atmosphere.

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SIAD S.p.A. EN (English) SDS Ref.: 00061_LIQ 4/10 Via San Bernardino, 92 I-24126



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

SDS reference: 00061_LIQ

SECTION 8: exposure controls/personal protection

8.1. Control parameters

OEL (Occupational Exposure Limits) : None available.

DNEL (Derived-No Effect Level) : None available.

PNEC (Predicted No-Effect Concentration) : None available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

: Provide adequate general and local exhaust ventilation.

Systems under pressure should be regularily checked for leakages.

Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The

following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

• Eye/face protection : Wear goggles and a face shield when transfilling or breaking transfer connections.

Standard EN 166 - Personal eye-protection - specifications.

Skin protection

- Hand protection : Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk.

Wear cold insulating gloves when transfilling or breaking transfer connections.

Standard EN 511 - Cold insulating gloves.

- Other : Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

• Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

• Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

: None necessary.

SECTION 9: physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa
 Colour
 Colourless.

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH : Not applicable for gases and gas mixtures.

 SIAD S.p.A.
 EN (English)
 SDS Ref.: 00061_LIQ
 5/10

Via San Bernardino, 92 I-24126 Bergamo Italia +39 035 328111



Revision date: 10/07/2017 Supersedes: 29/05/2015

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

SDS reference: 00061 LIQ

: -272 °C Melting point / Freezing point : -269 °C Boiling point

Flash point : Not applicable for gases and gas mixtures. : Not applicable for gases and gas mixtures. Evaporation rate

Flammability (solid, gas) : Non flammable. **Explosive limits** : Non flammable. Vapour pressure [20°C] : Not applicable. Vapour pressure [50°C] : Not applicable. Vapour density : Not applicable.

Relative density, liquid (water=1) : 0.12 Relative density, gas (air=1) : 0.14 Water solubility : 1.5 mg/l

Partition coefficient n-octanol/water (Log Kow) : Not applicable for inorganic gases.

Auto-ignition temperature : Non flammable. Decomposition temperature : Not applicable. Viscosity : Not known. Explosive properties : Not applicable. Oxidising properties : Not applicable.

9.2. Other information

: 4 g/mol Molar mass : -268 °C Critical temperature [°C]

SECTION 10: stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: None.

10.4. Conditions to avoid

: Avoid moisture in installation systems.

10.5. Incompatible materials

: For additional information on compatibility refer to ISO 11114.

Materials such as carbon steel, low alloy carbon steel and plastic become brittle at low temperatures and are subject to failure. Use appropriate materials compatible with the

cryogenic conditions present in refrigerated liquefied gas systems.

10.6. Hazardous decomposition products

: None.

SECTION 11: toxicological information

11.1. Information on toxicological effects

Acute toxicity : No toxicological effects from this product.

Skin corrosion/irritation : No known effects from this product. Serious eye damage/irritation : No known effects from this product.

SIAD S.p.A. EN (English) SDS Ref.: 00061_LIQ 6/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

: Not applicable for gases and gas mixtures.

SDS reference: 00061_LIQ

 Respiratory or skin sensitisation
 : No known effects from this product.

 Germ cell mutagenicity
 : No known effects from this product.

 Carcinogenicity
 : No known effects from this product.

 Toxic for reproduction: Fertility
 : No known effects from this product.

 Toxic for reproduction: unborn child
 : No known effects from this product.

 STOT-single exposure
 : No known effects from this product.

 STOT-repeated exposure
 : No known effects from this product.

SECTION 12: ecological information

12.1. Toxicity

Aspiration hazard

Assessment : No ecological damage caused by this product.

EC50 48h - Daphnia magna [mg/l] : No data available. EC50 72h - Algae [mg/l] : No data available. LC50 96 h - fish [mg/l] : No data available.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.

12.4. Mobility in soil

Assessment : No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects : Can cause frost damage to vegetation.

Effect on the ozone layer : None.
Effect on global warming : None.

SECTION 13: disposal considerations

13.1. Waste treatment methods

May be vented to atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Return unused product in original cylinder to supplier.

List of hazardous waste codes (from Commission Decision 2001/118/EC)

: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

13.2. Additional information

: External treatment and disposal of waste should comply with applicable local and/or national

regulations.

 SIAD S.p.A.
 EN (English)
 SDS Ref.: 00061_LIQ
 7/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

SDS reference: 00061_LIQ

SECTION 14: transport information

14.1. UN number

UN-No. : 1963

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) HELIUM, REFRIGERATED LIQUID

Transport by air (ICAO-TI / IATA-DGR) : Helium, refrigerated liquid

Transport by sea (IMDG) HELIUM, REFRIGERATED LIQUID

14.3. Transport hazard class(es)

Labelling



2.2 : Non-flammable, non-toxic gases.

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 3A
Hazard identification number : 22

Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other

carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable
Transport by air (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P203

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 202.
Cargo Aircraft only : 202.
Transport by sea (IMDG) : P203

 SIAD S.p.A.
 EN (English)
 SDS Ref.: 00061_LIQ
 8/10

Via San Bernardino, 92 I-24126 Bergamo Italia +39 035 328111



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

SDS reference: 00061_LIQ

Special transport precautions

 Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

SECTION 15: regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.

Seveso Directive : 2012/18/EU (Seveso III) : Not covered.

National regulations

National legislation : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes

: Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.

Abbreviations and acronyms

: ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC)

No 1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS# - Chemical Abstract Service number PPE - Personal Protection Equipment

LC50 - Lethal Concentration to 50 % of a test population

RMM - Risk Management Measures

PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative

STOT- SE: Specific Target Organ Toxicity - Single Exposure

CSA - Chemical Safety Assessment

EN - European Standard UN - United Nations

ADR - European Agreement concerning the International Carriage of Dangerous Goods by

Road

IATA - International Air Transport Association

IMDG code - International Maritime Dangerous Goods

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

SIAD S.p.A. EN (English) SDS Ref.: 00061_LIQ 9/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium (refrigerated liquid)

SDS reference: 00061_LIQ

Training advice

: The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Full text of H- and EUH-statements

Press. Gas (Ref. Liq.) H281 Gases under pressure : Refrigerated liquefied gas Contains refrigerated gas; may cause cryogenic burns or injury

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

SDS Ref.: 00061_LIQ