

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ



Danger

SECTION 1: identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Hydrogen bromide
 SDS no : 00068_LIQ
 Chemical description : Hydrogen bromide
 CAS-No. : 10035-10-6
 EC-No. : 233-113-0
 EC Index-No. : 035-002-00-0
 Registration-No. : 01-2119479072-39
 Chemical formula : HBr

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.
 Test gas/Calibration gas.
 Use for manufacture of electronic/photovoltaic components.
 Laboratory use.
 Contact supplier for more information on uses.
 Uses advised against : Consumer use.

1.3. Details of the supplier of the safety data sheet

Company identification : SIAD S.p.A.
 Via San Bernardino, 92
 I-24126 Bergamo Italia
 +39 035 328111
 www.siad.com
 siad_reach_clp@siad.com

1.4. Emergency telephone number

Emergency telephone number : Linea verde S.E.T. - from Italy 800452661 - International +39 0362512868 - 24 hours a day, 365 days a year

SECTION 2: hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Gases under pressure : Liquefied gas	H280
Health hazards	Acute toxicity (inhalation:gas) Category 3	H331
	Skin corrosion/irritation, Category 1A	H314
	Serious eye damage/eye irritation, Category 1	H318
	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335

2.2. Label elements

Safety Data Sheet


according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazard statements (CLP) :

H280 - Contains gas under pressure; may explode if heated.

H314 - Causes severe skin burns and eye damage.

H331 - Toxic if inhaled.

EUH071 - Corrosive to the respiratory tract.

EUH071 supersedes H335 when assigned in the classification.

Precautionary statements (CLP)

- Prevention : P260 - Do not breathe gas/vapours.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
- Response : P303+P361+P353+P315 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Get immediate medical advice / attention.
P304+P340+P315 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice / attention.
P305+P351+P338+P315 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice / attention.
- Storage : P403 - Store in a well-ventilated place.
P405 - Store locked up.

2.3. Other hazards

: None.

SECTION 3: composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrogen bromide	(CAS-No.) 10035-10-6 (EC-No.) 233-113-0 (EC Index-No.) 035-002-00-0 (Registration-No.) 01-2119479072-39	100	Press. Gas (Liq.), H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures : Not applicable

SECTION 4: first aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

- Skin contact : Remove contaminated clothing. Drench affected area with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- : May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.
- Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.
- Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

- : Obtain medical assistance.
- Treat with corticosteroid spray as soon as possible after inhalation.

SECTION 5: firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
Dry powder.
Carbon dioxide.
Foam.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None that are more hazardous than the product itself.

5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
- If possible, stop flow of product.
- Use water spray or fog to knock down fire fumes if possible.
- Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
- Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.
- Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

- : Try to stop release.
- Evacuate area.
- Monitor concentration of released product.
- Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
- Use chemically protective clothing.
- Ensure adequate air ventilation.
- Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
- Act in accordance with local emergency plan.
- Stay upwind.

6.2. Environmental precautions

- : Reduce vapour with fog or fine water spray.
- Try to stop release.

6.3. Methods and material for containment and cleaning up

- : Hose down area with water.
- Keep area evacuated and free from ignition sources until any spilled liquid has evaporated (ground free from frost).
- Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4. Reference to other sections

- : See also sections 8 and 13.

SECTION 7: handling and storage

7.1. Precautions for safe handling

Safe use of the product

- : The product must be handled in accordance with good industrial hygiene and safety procedures.
- Only experienced and properly instructed persons should handle gases under pressure.
- Consider pressure relief device(s) in gas installations.
- Ensure the complete gas system was (or is regularly) checked for leaks before use.
- Do not smoke while handling product.
- Avoid exposure, obtain special instructions before use.
- Avoid contact with aluminium.
- Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
- Installation of a cross purge assembly between the cylinder and the regulator is recommended.
- Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service.
- Avoid suck back of water, acid and alkalis.
- Do not breathe gas.
- Avoid release of product into atmosphere.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

Safe handling of the gas receptacle : Refer to supplier's container handling instructions.

- Do not allow backfeed into the container.
- Protect cylinders from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.
- Suck back of water into the container must be prevented.
- Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers.

- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8: exposure controls/personal protection

8.1. Control parameters

Hydrogen bromide (10035-10-6)

OEL : Occupational Exposure Limits

EU	STEL IOELV (EU) 15 min [mg/m ³]	6,7 mg/m ³
	STEL IOELV (EU) 15 min [ppm]	2 ppm
Austria	TWA (AT) OEL 8h [mg/m ³]	6,7 mg/m ³
	STEL (AT) OEL 15min [ppm]	2 ppm
	STEL (AT) OEL 15min [mg/m ³]	6,7 mg/m ³
	TWA (AT) OEL 8h [ppm]	2 ppm
Belgium	STEL (BE) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (BE) OEL 15min [ppm]	2 ppm
Bulgaria	STEL (BG) OEL 15min [mg/m ³]	6,7 mg/m ³
Estonia	STEL (EE) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (EE) OEL 15min [ppm]	2 ppm
France	STEL (FR) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (FR) OEL 15min [ppm]	2 ppm
	Note (FR)	Valeurs réglementaires indicatives
Germany	TWA (DE) OEL 8h [mg/m ³] TRGS 900	6,7 mg/m ³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

	Remark (TRGS 900)	DFG,EU,13
Greece	TWA (GR) OEL 8h [mg/m ³]	10 mg/m ³
	TWA (GR) OEL 8h [ppm]	3 ppm
	STEL (GR) OEL 15min [mg/m ³]	10 mg/m ³
	STEL (GR) OEL 15min [ppm]	3 ppm
ACGIH	ACGIH Ceiling (ppm)	2 ppm
	Remark (ACGIH)	URT irr
Italy	STEL (IT) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (IT) OEL 15min [ppm]	2 ppm
Latvia	STEL (LV) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (LV) OEL 15min [ppm]	2 ppm
Slovenia	TWA (SL) OEL 8h [mg/m ³]	6,7 mg/m ³
	TWA (SL) OEL 8h [ppm]	2 ppm
Spain	STEL (ES) OEL 15min [mg/m ³]	7 mg/m ³
	STEL (ES) OEL 15min [ppm]	2 ppm
	Notes	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).
Switzerland	STEL (CH) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (CH) OEL 15min [ppm]	2 ppm
	TWA (CH) OEL 8h [mg/m ³]	6,7 mg/m ³
	TWA (CH) OEL 8h [ppm]	2 ppm
	Remark (CH)	Lunge, OAW ^{KT HU} - OSHA, NIOSH
Netherlands	MAC STEL 15MIN (NL) [mg/m ³]	6,7 mg/m ³
United Kingdom	WEL - STEL - UK [mg/m ³]	10 mg/m ³
	WEL - STEL - UK [ppm]	3 ppm
Czech Republic	TWA (CZ) OEL 8h [mg/m ³]	1 mg/m ³
	TWA (CZ) OEL 8h [ppm]	0,3 ppm
	STEL (CZ) OEL 15min [mg/m ³]	6 mg/m ³
	STEL (CZ) OEL 15min [ppm]	1,81 ppm
Denmark	TWA (DK) OEL 8h [mg/m ³]	6,7 mg/m ³
	TWA (DK) OEL 8h [ppm]	2 ppm
	Anmærkninger (DK)	(2002); E (betyder, at stoffet har en EF-grænseværdi); L (markerer, at grænseværdien er en loftværdi, som ikke på noget tidspunkt må overskrides)
Finland	STEL (FI) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (FI) OEL 15min [ppm]	2 ppm
Hungary	STEL (HU) OEL 15min [mg/m ³]	6,7 mg/m ³
	Megjegyzések (HU)	m; l.
Iceland	STEL (IS) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (IS) OEL 15min [ppm]	2 ppm
Ireland	OEL (IE)-(15min reference period) [mg/m ³]	6,6 mg/m ³
	OEL (IE)-(15min reference period) [ppm]	2 ppm
	Notes (IE)	IOELV
Lithuania	STEL (LT) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (LT) OEL 15min [ppm]	2 ppm
	Remark (LT)	O
Malta	STEL (MT) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (MT) OEL 15min [ppm]	2 ppm
Norway	TWA (NO) OEL 8h [mg/m ³]	10 mg/m ³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

	TWA (NO) OEL 8h [ppm]	3 ppm
	Merknader (NO)	T
Romania	STEL (RO) OEL 15min [mg/m ³]	6,7 mg/m ³
	STEL (RO) OEL 15min [ppm]	2 ppm
Slovakia	Maximum permissible exposure limit, average, 8h (SK) [mg/m ³]	1100 mg/m ³
	Maximum permissible exposure limit, average, 8h (SK) [ppm]	200 ppm
Sweden	TWA (SV) OEL 8h [mg/m ³]	3,5 mg/m ³ 3,5 mg/m ³
	TWA (SV) OEL 8h [ppm]	1 ppm 1 ppm
	STEL (SV) OEL 15min [mg/m ³]	7 mg/m ³ 7 mg/m ³
	STEL (SV) OEL 15min [ppm]	2 ppm 2 ppm
	Ceiling value (SV) OEL [mg/m ³]	7 mg/m ³
	Ceiling value (SV) OEL [ppm]	2 ppm

Hydrogen bromide (10035-10-6)

DNEL: Derived no effect level (Workers)

Acute - local effects, inhalation	6,7 mg/m ³
Acute - systemic effects, inhalation	6,7 mg/m ³
Long-term - local effects, inhalation	6,7 mg/m ³
Long-term - systemic effects, inhalation	6,7 mg/m ³

Hydrogen bromide (10035-10-6)

PNEC: Predicted no effect concentration

Aqua (freshwater)	0,019 mg/l
-------------------	------------

8.2. Exposure controls

8.2.1. Appropriate engineering controls

- : Provide adequate general and local exhaust ventilation.
- Product to be handled in a closed system.
- Systems under pressure should be regularly checked for leakages.
- Ensure exposure is below occupational exposure limits (where available).
- Gas detectors should be used when toxic gases may be released.
- Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection
 - : Wear goggles and a face shield when transfilling or breaking transfer connections.
 - Standard EN 166 - Personal eye-protection - specifications.
 - Provide readily accessible eye wash stations and safety showers.

- Skin protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

- Hand protection : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk.
Wear cold insulating gloves when transfilling or breaking transfer connections.
Standard EN 511 - Cold insulating gloves.
Wear chemically resistant protective gloves.
Standard EN 374 - Protective gloves against chemicals.
Hydrogenated Nitrile -Butadiene rubber (HNBR).
Natural rubber (NR).
- Other : Keep suitable chemically resistant protective clothing readily available for emergency use.
Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals.
Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
Recommended: Filter E (yellow).
Gas filters do not protect against oxygen deficiency.
Standard EN 14387 - Gas filter(s), combined filter(s) and full face mask - EN 136.
Keep self contained breathing apparatus readily available for emergency use.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
- Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

- : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas
- Colour : Colourless. Gives off white fumes in moist air.

Odour : Pungent.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH : If dissolved in water pH-value will be affected.

Melting point / Freezing point : -87 °C

Boiling point : -66,7 °C

Flash point : Not applicable for gases and gas mixtures.

Evaporation rate : Not applicable for gases and gas mixtures.

Flammability (solid, gas) : Non flammable.

Explosive limits : Non flammable.

Vapour pressure [20°C] : 21 bar(a)

Vapour pressure [50°C] : 42 bar(a)

Vapour density : Not applicable.

Relative density, liquid (water=1) : 2,2

Relative density, gas (air=1) : 2,8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

Water solubility	: 700000 mg/l
Partition coefficient n-octanol/water (Log Kow)	: 0,63
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Viscosity	: Not known.
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.

9.2. Other information

Molar mass	: 81 g/mol
Critical temperature [°C]	: 90 °C
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: None.

10.4. Conditions to avoid

: Avoid moisture in installation systems.

10.5. Incompatible materials

: Reacts with most metals in the presence of moisture, liberating hydrogen, an extremely flammable gas.
With water causes rapid corrosion of some metals.
Reacts with water to form corrosive acids.
May react violently with alkalis.
Moisture.
For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: toxicological information

11.1. Information on toxicological effects

Acute toxicity : Toxic if inhaled.
Delayed fatal pulmonary oedema possible.

LC50 inhalation rat (ppm) 1430 ppm/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : No known effects from this product.

Germ cell mutagenicity : No known effects from this product.

Carcinogenicity : No known effects from this product.

Toxic for reproduction : Fertility : No known effects from this product.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: Severe corrosion to the respiratory tract at high concentrations.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

SECTION 12: ecological information

12.1. Toxicity

Assessment : Classification criteria are not met.

EC50 48h - Daphnia magna [mg/l] : 19 mg/l

EC50 72h - Algae [mg/l] : 130 mg/l

LC50 96 h - fish [mg/l] : 65 mg/l

12.2. Persistence and degradability

Assessment : Not applicable for inorganic gases.

12.3. Bioaccumulative potential

Assessment : Not expected to bioaccumulate due to the low log Kow (log Kow < 4).
Refer to section 9.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.
Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.

Effect on the ozone layer : None.

Effect on global warming : No known effects from this product.

SECTION 13: disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.

Must not be discharged to atmosphere.

Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere.

Gas may be scrubbed in alkaline solution under controlled conditions to avoid violent reaction.

Ensure that the emission levels from local regulations or operating permits are not exceeded.

Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.eu> for more guidance on suitable disposal methods.

Return unused product in original cylinder to supplier.

List of hazardous waste codes (from Commission Decision 2001/118/EC) : 16 05 04 *: Gases in pressure containers (including halons) containing dangerous substances.

13.2. Additional information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: transport information

14.1. UN number

UN-No. : 1048

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : HYDROGEN BROMIDE, ANHYDROUS

Transport by air (ICAO-TI / IATA-DGR) : Hydrogen bromide, anhydrous

Transport by sea (IMDG) : HYDROGEN BROMIDE, ANHYDROUS

14.3. Transport hazard class(es)

Labelling



2.3 : Toxic gases.

8 : Corrosive substances.

Transport by road/rail (ADR/RID)

Class : 2
 Classification code : 2TC
 Hazard identification number : 268
 Tunnel Restriction : C/D - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category D and E

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.3 (8)
 Emergency Schedule (EmS) - Fire : F-C
 Emergency Schedule (EmS) - Spillage : S-U

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable
 Transport by air (ICAO-TI / IATA-DGR) : Not applicable
 Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
 Transport by air (ICAO-TI / IATA-DGR) : None.
 Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200
 Transport by air (ICAO-TI / IATA-DGR)
 Passenger and Cargo Aircraft : Forbidden.
 Cargo Aircraft only : Forbidden.
 Transport by sea (IMDG) : P200

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrogen bromide

SDS reference: 00068_LIQ

Abbreviations and acronyms

: ATE - Acute Toxicity Estimate
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
EINECS - European Inventory of Existing Commercial Chemical Substances
CAS# - Chemical Abstract Service number
PPE - Personal Protection Equipment
LC50 - Lethal Concentration to 50 % of a test population
RMM - Risk Management Measures
PBT - Persistent, Bioaccumulative and Toxic
vPvB - Very Persistent and Very Bioaccumulative
STOT- SE : Specific Target Organ Toxicity - Single Exposure
CSA - Chemical Safety Assessment
EN - European Standard
UN - United Nations
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA - International Air Transport Association
IMDG code - International Maritime Dangerous Goods
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
WGK - Water Hazard Class

Training advice

: Users of breathing apparatus must be trained.
Ensure operators understand the toxicity hazard.

Full text of H- and EUH-statements

Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
EUH071	Corrosive to the respiratory tract

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press.
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document